



### SPECIFICATION



Net Weight: 85g ± 5g

Part No.	Rated Voltage (V)	Speed (RPM)	Current (Amp)	Voltage Range (V)	Air Flow (CFM)	Static Pressure (inch-H <sub>2</sub> O)	Noise (dBA)	Bearing	Life Expectancy (@25°C / Hour)
HS-8025-S12L	12	2000	0.10	07~15	28.9	0.10	24	Sleeve	21,000
HS-8025-B12L								One Ball & One Sleeve	80,000
HS-8025-D12L								Dual Balls	85,000
HS-8025-S12M	12	2500	0.15	07~15	33.4	0.16	27	Sleeve	20,500
HS-8025-B12M								One Ball & One Sleeve	77,500
HS-8025-D12M								Dual Balls	82,500
HS-8025-S12H	12	3200	0.19	07~15	43.3	0.23	31	Sleeve	19,800
HS-8025-B12H								One Ball & One Sleeve	74,000
HS-8025-D12H								Dual Balls	79,000
HS-8025-S24L	24	2000	0.08	15~27	28.9	0.10	24	Sleeve	21,000
HS-8025-B24L								One Ball & One Sleeve	80,000
HS-8025-D24L								Dual Balls	85,000
HS-8025-S24M	24	2500	0.12	15~27	33.4	0.16	27	Sleeve	20,500
HS-8025-B24M								One Ball & One Sleeve	77,500
HS-8025-D24M								Dual Balls	82,500
HS-8025-S24H	24	3200	0.16	15~27	43.3	0.23	31	Sleeve	19,800
HS-8025-B24H								One Ball & One Sleeve	74,000
HS-8025-D24H								Dual Balls	79,000

★ High Pace reserve the rights to change data without notice.

★ Custom specifications are available on request.