



SPECIFICATION



Net Weight: 155g ± 10g

Part No.	Rated Voltage (V)	Speed (RPM)	Current (Amp)	Voltage Range (V)	Air Flow (CFM)	Static Pressure (inch-H ₂ O)	Noise (dBA)	Bearing	Life Expectancy (@25°C / Hour)
HS-1225-S12L	12	1800	0.25	07~15	54	0.14	26	Sleeve	21,200
HS-1225-B12L								One Ball & One Sleeve	81,000
HS-1225-D12L								Dual Balls	86,000
HS-1225-S12M	12	2200	0.35	07~15	68	0.16	30	Sleeve	20,800
HS-1225-B12M								One Ball & One Sleeve	79,000
HS-1225-D12M								Dual Balls	84,000
HS-1225-S12H	12	2700	0.60	07~15	77	0.23	34	Sleeve	20,300
HS-1225-B12H								One Ball & One Sleeve	77,500
HS-1225-D12H								Dual Balls	81,500
HS-1225-S24L	24	1800	0.15	15~26	54	0.14	26	Sleeve	21,200
HS-1225-B24L								One Ball & One Sleeve	81,000
HS-1225-D24L								Dual Balls	86,000
HS-1225-S24M	24	2400	0.25	15~26	68	0.16	30	Sleeve	20,800
HS-1225-B24M								One Ball & One Sleeve	79,000
HS-1225-D24M								Dual Balls	84,000
HS-1225-S24H	24	3000	0.35	15~26	77	0.23	34	Sleeve	20,300
HS-1225-B24H								One Ball & One Sleeve	77,500
HS-1225-D24H								Dual Balls	81,500

★ High Pace reserve the rights to change data without notice.

★ Custom specifications are available on request.