



SPECIFICATION



Net Weight: 19g ± 2g

Part No.	Rated Voltage (V)	Speed (RPM)	Current (Amp)	Voltage Range (V)	Air Flow (CFM)	Static Pressure (inch-H ₂ O)	Noise (dBA)	Bearing	Life Expectancy (@25°C / Hour)
HP-5010-S05L	05	3000	0.08	04~07	7.2	0.18	22	Sleeve	18,000
HP-5010-B05L								One Ball & One Sleeve	65,000
HP-5010-D05L								Dual Balls	70,000
HP-5010-S05M	05	4000	0.11	04~07	9.3	0.20	23	Sleeve	17,000
HP-5010-B05M								One Ball & One Sleeve	60,000
HP-5010-D05M								Dual Balls	65,000
HP-5010-S12L	12	3000	0.06	07~15	7.2	0.18	22	Sleeve	18,000
HP-5010-B12L								One Ball & One Sleeve	65,000
HP-5010-D12L								Dual Balls	70,000
HP-5010-S12M	12	4000	0.08	07~15	9.3	0.20	23	Sleeve	17,000
HP-5010-B12M								One Ball & One Sleeve	60,000
HP-5010-D12M								Dual Balls	65,000
HP-5010-S12H	12	5000	0.11	07~15	10.6	0.22	26	Sleeve	16,000
HP-5010-B12H								One Ball & One Sleeve	55,000
HP-5010-D12H								Dual Balls	60,000
HP-5010-S24L	24	3000	0.05	15~27	7.2	0.18	22	Sleeve	18,000
HP-5010-B24L								One Ball & One Sleeve	65,000
HP-5010-D24L								Dual Balls	70,000
HP-5010-S24M	24	4000	0.07	15~27	9.3	0.20	23	Sleeve	17,000
HP-5010-B24M								One Ball & One Sleeve	60,000
HP-5010-D24M								Dual Balls	65,000
HP-5010-S24H	24	5000	0.10	15~27	10.6	0.22	26	Sleeve	16,000
HP-5010-B24H								One Ball & One Sleeve	55,000
HP-5010-D24H								Dual Balls	60,000

★ High Pace reserve the rights to change data without notice.

★ Custom specifications are available on request.