



SPECIFICATION



Net Weight: 30g ± 2g

Part No.	Rated Voltage (V)	Speed (RPM)	Current (Amp)	Voltage Range (V)	Air Flow (CFM)	Static Pressure (inch-H ₂ O)	Noise (dBA)	Bearing	Life Expectancy (@25°C / Hour)
HP-6015-S05L	05	3000	0.11	04~07	9.8	0.18	28	Sleeve	20,000
HP-6015-B05L								One Ball & One Sleeve	75,000
HP-6015-D05L								Dual Balls	80,000
HP-6015-S05M	05	3600	0.18	04~07	14.1	0.25	29	Sleeve	19,500
HP-6015-B05M								One Ball & One Sleeve	72,500
HP-6015-D05M								Dual Balls	77,500
HP-6015-S12L	12	3000	0.07	08~15	9.8	0.18	28	Sleeve	20,000
HP-6015-B12L								One Ball & One Sleeve	75,000
HP-6015-D12L								Dual Balls	80,000
HP-6015-S12M	12	3600	0.11	08~15	14.1	0.25	29	Sleeve	19,500
HP-6015-B12M								One Ball & One Sleeve	72,500
HP-6015-D12M								Dual Balls	77,500
HP-6015-S12H	12	4200	0.18	08~15	16.5	0.28	31	Sleeve	17,000
HP-6015-B12H								One Ball & One Sleeve	69,000
HP-6015-D12H								Dual Balls	74,000
HP-6015-S24L	24	3000	0.06	15~27	9.8	0.18	28	Sleeve	20,000
HP-6015-B24L								One Ball & One Sleeve	75,000
HP-6015-D24L								Dual Balls	80,000
HP-6015-S24M	24	3600	0.09	15~27	14.1	0.25	29	Sleeve	19,500
HP-6015-B24M								One Ball & One Sleeve	72,500
HP-6015-D24M								Dual Balls	77,500
HP-6015-S24H	24	4200	0.15	15~27	16.5	0.28	31	Sleeve	17,000
HP-6015-B24H								One Ball & One Sleeve	69,000
HP-6015-D24H								Dual Balls	74,000

★ High Pace reserve the rights to change data without notice.

★ Custom specifications are available on request.