



SPECIFICATION



Net Weight: 65g ± 5g

Part No.	Rated Voltage (V)	Speed (RPM)	Current (Amp)	Voltage Range (V)	Air Flow (CFM)	Static Pressure (inch-H ₂ O)	Noise (dBA)	Bearing	Life Expectancy (@25°C / Hour)
HS-6025-S12L	12	2800	0.09	07~15	17.2	0.15	23	Sleeve	20,800
HS-6025-B12L								One Ball & One Sleeve	76,000
HS-6025-D12L								Dual Balls	81,000
HS-6025-S12M	12	3500	0.15	07~15	19.8	0.20	27	Sleeve	19,500
HS-6025-B12M								One Ball & One Sleeve	72,500
HS-6025-D12M								Dual Balls	77,500
HS-6025-S12H	12	4000	0.19	07~15	22.6	0.25	31	Sleeve	19,000
HS-6025-B12H								One Ball & One Sleeve	70,000
HS-6025-D12H								Dual Balls	75,000
HS-6025-S24L	24	2800	0.07	15~27	17.2	0.15	23	Sleeve	20,800
HS-6025-B24L								One Ball & One Sleeve	76,000
HS-6025-D24L								Dual Balls	81,000
HS-6025-S24M	24	3500	0.12	15~27	19.8	0.20	27	Sleeve	19,500
HS-6025-B24M								One Ball & One Sleeve	72,500
HS-6025-D24M								Dual Balls	77,500
HS-6025-S24H	24	4000	0.16	15~27	22.6	0.25	31	Sleeve	19,000
HS-6025-B24H								One Ball & One Sleeve	70,000
HS-6025-D24H								Dual Balls	75,000

★ High Pace reserve the rights to change data without notice.

★ Custom specifications are available on request.